

MATERIAL SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Ecoment Corundum

1.2 Details of the supplier

Manufacturer/Supplier: Effco finishes and technologies pvt
ltd Thirumal Ind estate, Hinjewadei, Phase II,Pune -411057
Tel.: +91 9967060596

1.3 Emergency telephone number:

Phone: +91 9850784185/ +91 9967060596
email: warat@effcoindia.com
kunal@effcoindia.com

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R41: Risk of serious damage to eyes.



N; Dangerous for the environment

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10-67: Flammable. Vapours may cause drowsiness and dizziness.

MATERIAL SAFETY DATA SHEET

·
·
· **Hazard statements** ·

H226 *Flammable liquid and vapour.*
H315 *Causes skin irritation.*
H318 *Causes serious eye damage.*
H410 *Very toxic to aquatic life with long lasting effects.*

· **Precautionary statements** ·



P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
P303+P361+P353 *-IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*
P305+P351+P338 *-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P310 *Immediately call a doctor.*
P403+P235 *Store in a well-ventilated place. Keep cool.*
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

* **SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

· **Description:** *Mixture consisting of the following components with harmless additives.*

· **Dangerous components:**

CAS: 7440-66-6	zinc powder -zinc dust (stabilized) 	50-<65%
CAS: 7429-90-5	aluminium powder 	10.0-15.0%

MATERIAL SAFETY DATA SHEET

CAS: 64742-94-5	Solvent naphtha (petroleum), heavy arom.	5.0-10.0%
CAS : 92045-53-9	Solvent Naptha Petroleum light arom	2.0- 3.0%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information**

Personal protection for the First Aider.

Do not leave affected persons unsupervised.

Take affected persons out of danger area and instruct to lie down.

· **After inhalation** *Supply fresh air; consult doctor in case of symptoms.*

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact**

· *Rinse opened eye for several minutes under running water. Then consult doctor. Protect unharmed eye.*

· *After swallowing Rinse out mouth and then drink plenty of water.*

MATERIAL SAFETY DATA SHEET

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing agents Alcohol-resistant foam
- For safety reasons unsuitable extinguishing agents Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

- Can be released in case of fire
- Nitrogen oxides (NO_x)
- Carbon monoxide (CO)

5.3 Advice for firefighters

Protective equipment: Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment, and emergency procedures

- Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- Keep away from ignition sources
- Wear protective clothing.

6.2 Environmental precautions:

- Do not allow product to reach sewage system or water bodies.
- Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

- Absorb with liquid-binding material (sand, diatomite, sawdust).
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Keep containers tightly sealed.
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

- Storage
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility: Not required.

MATERIAL SAFETY DATA SHEET

- Further information about storage conditions: Keep container tightly sealed.
- Storage class 3

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

7429-90-5 aluminium powder (stabilized)

TLV	Long-term exposure – 8 hrs
TWA	10.0 mg/m ³

7440-66-6 zinc powder -zinc dust (stabilized)

TWA (Inhalable)	10.0 mg/m ³ 5.0 mg/m ³ (long term)
TWA (Respirable)	Systematic)4 mg/m ³

64742-94-5 Solvent naphtha (petroleum), heavy aroma.

TWA	100 mg/m ³
-----	-----------------------

92045-53-9 Solvent Naptha Petroleum light aroma

TWA	100 mg/m ³
-----	-----------------------

MATERIAL SAFETY DATA SHEET

Additional information: The lists that were valid during the compilation were used as basis

8.2 Exposure controls

· **Personal protective equipment**

· **General protective and hygienic measures**

The usual precautionary measures should be adhered to in handling the chemicals.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes.

· **Breathing equipment:**



Only during spraying without adequate removal by suction.

· **Protection of hands:**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

To avoid skin problems, reduce the wearing of gloves to the required minimum.

Avoid direct contact with the chemical/ the product.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

MATERIAL SAFETY DATA SHEET

SECTION 9: Physical and chemical properties

· 9.1 Information on physical and chemical properties

· Appearance:

· Form:	<i>Fluid</i>
· Color:	<i>According to product specification</i>
· Smell:	<i>Solvent like</i>

· **PH-value:** *Not applicable*

· Change in condition

· Melting point/Melting range:	<i>Not determined</i>
· Boiling point/Boiling range:	<i>120 °C</i>

· **Flash point:** *34 °C*

· **Inflammability (solid, gaseous)** *Not applicable.*

· **Ignition temperature:** *400 °C*

· **Decomposition temperature:** *Not determined*

· **Danger of explosion:** *Product is not explosive. However, formation of explosive steam/air mixtures is possible.*

· Critical values for explosion:

· Lower:	<i>0.6 Vol %</i>
· Upper:	<i>28.2 Vol %</i>

· **Vapor pressure at 20 °C:** *1.4 hPa*

· Density at 20 °C	<i>1.3 gm/cm³</i>
· Relative density	<i>Not determined.</i>
· Vapour density	<i>Not determined</i>
· Evaporation rate	<i>Not determined.</i>

· **Solubility in / Miscibility with Water:** *Not miscible*

MATERIAL SAFETY DATA SHEET

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

7440-66-6 zinc powder -zinc dust (stabilized)

Oral	LD50	>2000 mg/kg (Muroidea)
Inhalative	LC50/4 h	5.41 mg/L (Muroidea)

64742-94-5 Solvent naphtha (petroleum), heavy arom.

Oral	LD50	>5000 mg/kg
Dermal	LD50	>2000 mg/kg

92045-53-9 Solvent Naptha Petroleum light arom

Oral	LD50	>2000 mg/kg
Dermal	LD50	>2000 mg/kg

TOXICOLOGICAL INFORMATION

No data is available for this preparation, which is classified according to the calculation method of EC Directives using information about the individual components.

INHALATION In high concentrations, vapors may irritate throat and respiratory system and cause coughing. Vapor may affect central nervous system and cause headache, discomfort, vomiting or intoxication.

INGESTION Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract.

SKIN CONTACT Irritating to skin. Repeated exposure may cause skin dryness or cracking. Hydrolyses on contact with skin moisture forms solid polymeric titanium compounds which may be deposited on the surface.

EYE CONTACT Irritating and may cause redness and pain.

MATERIAL SAFETY DATA SHEET

*

SECTION 12: Ecological information

- **ECOTOXICITY**
- *The product is not expected to be hazardous to the environment.*
- **BIOACCUMULATION**
- *Neither the product or its hydrolysis products are expected to bioaccumulate.*
- **DEGRADABILITY**
- *The product is degraded completely by hydrolysis.*

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to disposers of hazardous waste.

Recommendation: Disposal must be made according to official regulations.

MATERIAL SAFETY DATA SHEET

*

SECTION 14: Transport information

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR	<i>PAINT, ENVIRONMENTALLY HAZARDOUS</i>
· IMDG	<i>PAINT (zinc powder -zinc dust (stabilized), Solvent Naphtha), MARINE POLLUTANT</i>
· IATA	<i>PAINT</i>
· 14.3 Transport hazard class(es)	
· ADR	
· Class	<i>3 (F1) Flammable liquids.</i>
· Label	<i>3</i>
· IMDG	
· Class	<i>3 Flammable liquids.</i>
· Label	<i>3</i>
· IATA	
· Class	<i>3 Flammable liquids.</i>
· Label	<i>3</i>
· 14.4 Packing group	
· ADR, IMDG, IATA	<i>III</i>
· 14.5 Environmental hazards:	
	<i>Product contains environmentally hazardous substances: zinc powder -zinc dust (stabilized)</i>
· Marine pollutant:	<i>Yes Symbol (fish and tree)</i>

MATERIAL SAFETY DATA SHEET

- | | |
|--|--|
| · Special marking (ADR): | Symbol (fish and tree) |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · UN "Model Regulation": | UN1263, PAINT, ENVIRONMENTALLY HAZARDOUS, 3, III |

SECTION 15: Regulatory information

- **15.1 Safety, health, and environmental regulations/legislation specific for the substance or mixture**
- **National regulations**
- **Decree to be applied in case of technical fault:**
Critical quantity values according to the regulations on accidents should be adhered to.
- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **Other regulations, limitations and prohibitive regulations**

- | |
|--|
| · Substances of very high concern (SVHC) according to REACH, Article 57 |
|--|

None of the ingredients is listed.

- | |
|---------------------------|
| · REACH /Annex XIV |
|---------------------------|

None of the ingredients is listed.

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H260 In contact with water releases flammable gases which may ignite spontaneously.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.

MATERIAL SAFETY DATA SHEET

- R15 Contact with water liberates extremely flammable gases.*
- R20 Harmful by inhalation.*
- R36 Irritating to eyes.*
- R36/37/38 Irritating to eyes, respiratory system and skin.*
- R37 Irritating to respiratory system.*
- R37/38 Irritating to respiratory system and skin.*
- R41 Risk of serious damage to eyes.*
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
- R65 Harmful: may cause lung damage if swallowed.*
- R66 Repeated exposure may cause skin dryness or cracking.*
- R67 Vapours may cause drowsiness and dizziness.*