





6-Lobe Pin - Countersunk Self Drilling Screws



Self Drilling Screws Technical Info (mm)

HEAD STYLE		GAUGE	No. 8	No. 10	No. 12
			4.2mm	4.8mm	5.5mm
COUNTERSUNK HEAD			7.9	9.3	10.6
		I	3.0	3.2	3.7
POINT SIZE			2	3	3
MATERIAL THICKNESS Mild Steel up to (mm)			1 + 2	2 + 2	2 + 3

All sizes shown are without min and max tolerances and are guide sizes.

Material and Finish

Material: Steel C1022
Heat Treatment: Hardened
Finish: Delta Protekt

Part Numbers, Size & Tooling


LENGTH		1/2"	3/4"	1"	1 1/2"	2"	DRIVER SIZE
		13mm	19mm	25mm	38mm	50mm	
8	4.2mm	RTCD08D -DP	RTCD08F -DP	RTCD08G -DP	RTCD08I -DP		T20
10	4.8mm		RTCD10F -DP	RTCD10G -DP	RTCD10I -DP	RTCD10J -DP	T25
12	5.5mm			RTCD12G -DP	RTCD12I -DP	RTCD12J -DP	T27

Additional Information


Patented Product: Hafren Fasteners

Installation: 6-Lobe Pin - see video

Removal: 2-Way Removable Screw



- ✓ No need to pre-drill
- ✓ Fast installation
- ✓ 6-Lobe Pin security drive
- ✓ Delta Protekt® Coated Steel
- ✓ Pan and Countersunk Head



Every effort has been made to ensure the accuracy of information provided in this datasheet. Hafren Fasteners cannot warrant the information however, expressly or implied, and any liability arising from it is expressly excluded. Customers must satisfy themselves as to the suitability of products and the technical information relating to them, and it is recommended that you conduct your own tests to establish suitability. All sizes shown are in mm without min and max tolerances and are guide sizes. Hafren Fasteners reserve the right to change/alter sizes without notice. This does not effect your statutory rights.