





## 6-Lobe Pin - Pan Head Self Drilling Screws



### Self Drilling Screws Technical Info (mm)

HEAD STYLE		GAUGE	No. 8	No. 10	No. 12
			4.2mm	4.8mm	5.5mm
PAN HEAD			7.9	9.3	10.6
			2.9	3.4	3.9
POINT SIZE			2	3	3
MATERIAL THICKNESS Mild Steel up to (mm)			1 + 2	2 + 2	2 + 3

All sizes shown are without min and max tolerances and are guide sizes.

### Material and Finish

**Material:** Steel C1022  
**Heat Treatment:** Hardened  
**Finish:** Delta Protekt

### Part Numbers, Size & Tooling

GAUGE	LENGTH	1/2"	3/4"	1"	1 1/2"	2"	DRIVER SIZE
		13mm	19mm	25mm	38mm	50mm	
8	4.2mm	RTPD08D -DP	RTPD08F -DP	RTPD08G -DP	RTPD08I -DP		T20
10	4.8mm		RTPD10F -DP	RTPD10G -DP	RTPD10I -DP	RTPD10J -DP	T25
12	5.5mm			RTPD12G -DP	RTPD12I -DP	RTPD12J -DP	T27


\*All parts Packed in 100pcs - Please see below Pack Dimension guide for sizes


### Additional Information

**Patented Product:** Hafren Fasteners

**Installation:** 6-Lobe Pin - see video

**Removal:** 2-Way Removable Screw

-  **Self Drillers**
- ✓ No need to pre-drill
- ✓ Fast installation
- ✓ 6-Lobe Pin security drive
- ✓ Delta Protekt® Coated Steel
- ✓ Pan and Countersunk Head



Every effort has been made to ensure the accuracy of information provided in this datasheet. Hafren Fasteners cannot warrant the information however, expressly or implied, and any liability arising from it is expressly excluded. Customers must satisfy themselves as to the suitability of products and the technical information relating to them, and it is recommended that you conduct your own tests to establish suitability. All sizes shown are in mm without min and max tolerances and are guide sizes. Hafren Fasteners reserve the right to change/alter sizes without notice. This does not effect your statutory rights.