


5-Lobe Pin



5-Lobe Pin - Countersunk Head Machine Screws - A4-70 Stainless Steel



Dimensions (mm)

SCREW TYPE 5-LOBE PIN	METRIC MACHINE SCREWS						
	DIMENSIONS		M3	M4	M5	M6	M8
COUNTERSUNK HEAD			5.8	8.0	10.0	12.0	16.0
		I	1.7	2.3	2.8	3.3	4.4

Material and Finish

Material: A4-70 Minimum Tensile Strength 700N/mm²
Heat Treatment: None
Finish: Passivated

Size & Part Numbers

LENGTH GAUGE	6 mm	8 mm	10 mm	12 mm	16 mm	20 mm	25 mm	30 mm	40 mm	DRIVER SIZE
	M3	FLPCM 0306-A4		FLPCM 0310-A4						
M4		FLPCM 0408-A4	FLPCM 0410-A4	FLPCM 0412-A4	FLPCM 0416-A4	FLPCM 0420-A4	FLPCM 0425-A4			F20-B
M5		FLPCM 0506-A4	FLPCM 0510-A4	FLPCM 0512-A4	FLPCM 0516-A4	FLPCM 0520-A4	FLPBM 0525-A4	FLPBM 0530-A4	FLPBM 0540-A4	F25-B
M6				FLPCM 0612-A4	FLPCM 0616-A4	FLPCM 0620-A4	FLPCM 0625-A4	FLPCM 0630-A4	FLPCM 0640-A4	F30-B
M8						FLPCM 0820-A4			FLPCM 0840-A4	F40-B

Additional Information

Patented Product: Hafren Fasteners
Installation: 5-Lobe Pin - see video
Removal: 2-Way Removable Screw

- ✓ High torque drive
- ✓ 5-Lobe with Pin design
- ✓ A4-70 Stainless Steel
- ✓ Button and Countersunk Head
- ✓ Metric Machine Screws and Self Tapping Screws

Every effort has been made to ensure the accuracy of information provided in this catalogue. Hafren Fasteners cannot warrant the information however, expressly or implied, and any liability arising from it is expressly excluded. Customers must satisfy themselves as to the suitability of products and the technical information relating to them, and it is recommended that you conduct your own tests to establish suitability. All sizes shown are in mm without min and max tolerances and are guide sizes. Hafren Fasteners reserve the right to change/alter sizes without notice. This does not effect your statutory rights.