




## Shear Nut - Galvanised



### Dimensions (mm)

| DIMENSIONS | SIZE | M8   | M10  | M12  | M16  | M20  |
|------------|------|------|------|------|------|------|
|            | AF   |      | 17.0 | 19.0 | 22.0 | 24.0 |
| B          |      | 16.8 | 18.9 | 21.9 | 23.8 | 31.8 |
| C          |      | N/A  | N/A  | N/A  | N/A  | 2.9  |
| D          |      | 7.2  | 9.2  | 9.2  | 11.5 | 18.8 |

### Material and Finish

**Material:** Mild Steel  
**Heat Treatment:** None  
**Finish:** Galvanised

### Part Numbers, Shear Torque & Box Quantities

| PART NUMBER  | SIZE  | M8    | M10     | M12     | M16     | M20     |
|--------------|-------|-------|---------|---------|---------|---------|
|              |       |       | SHN08-G | SHN10-G | SHN12-G | SHN16-G |
| SHEAR TORQUE | lb/ft | 10-15 | 23-28   | 38-44   | 54-60   | 72-82   |
|              | nm    | 14-20 | 31-38   | 52-60   | 74-82   | 100-113 |

### Additional Information

**Installation:** Uses standard hex spanners or socket

**See Video:** [\[Video Link\]](#)

**Removal:** 1-Way Permanent fixing only

**Shear Nuts**

- ✓ High security permanent fixing
- ✓ Installed using standard tools
- ✓ Leaves a tamper resistant cone

Every effort has been made to ensure the accuracy of information provided in this catalogue. Hafren Fasteners cannot warrant the information however, expressly or implied, and any liability arising from it is expressly excluded. Customers must satisfy themselves as to the suitability of products and the technical information relating to them, and it is recommended that you conduct your own tests to establish suitability. All sizes shown are in mm without min and max tolerances and are guide sizes. Hafren Fasteners reserve the right to change/alter sizes without notice. This does not effect your statutory rights.